

Technical Data

Acrypol + Black Roof Coating

Ref. RC 3005

Purpose	A high performance waterproof roof coating for use on most types of conventional roof structures, which can be applied on damp substrates in inclement weather conditions. Contains fibres to bridge cracks in substrate.	
Composition	Acrylic resin pigmented with specially selected opacifying pigments, fillers and fibres in a suitable solvent.	
Application	Brush or squeegee. For spraying application, consult manufacturer.	
Volume Solids Percentage	50% ± 2%	
Recommended Minimum Film Thickness	1000 microns wet	500 microns dry
Theoretical Spreading Rate At Above Thickness	1sq. metre per kg at 500 microns dry film thickness.	
Drying Time	24 hours at 18°C - 21°C. Drying time will be extended at lower temperatures.	
Recoating Time	24 hours at 18°C - 21°C.	
Cleaning Solvent	AC 4001 Acrypol Cleaner.	
Storage Properties	Several years in original unopened containers.	
Flash Point	> 32°C & ≤ 55°C.	
Colour	Black.	
Finish	Sheen.	
Surface Preparation	Refer to specification.	
Suitable Further Coating	Coat on coat.	
Pack Availability	5 kg and 20 kg.	
Safety Precautions	See Product Safety Data Sheet: Acrypol Plus	
Additional Data	The details and information contained herein, are to the best of our knowledge correct but may from time to time be subject to revision. We will endeavour to keep customers informed of any changes that may occur but we advise that if in any doubt, contact is made with the manufacturer to establish the data is of the latest available. We would point out that whilst we have striven to ensure the details are as accurate as possible, we offer no guarantee as application conditions and techniques are beyond our control.	