

Product Information

Ultimate All-In-One Filler & Caulk



PERFORMANCE

Application temperature:	+5°C to +40°C (Applies to both environment and substrate)
Service temp range:	-20°C to +70°C.
Tack free time:	15 minutes to 1 hour depending on ambient conditions.
Curing time:	2 - 24 hours depending on application
Paintable:	With water-based and solvent paints
Elongation at Break:	≥ 100%
Resistance to flow:	≤ 3%
Release of chemicals:	None
Colour:	White
Cracking:	None
Smell:	Almost odourless
Packaging:	Cartridge
Volume:	310 ml
Use:	Interior, including: <ul style="list-style-type: none"> • Skirting boards • Plasterwork • Architrave • Door and window frames • Coving
Adhesion:	Good adhesion to: <ul style="list-style-type: none"> • Concrete • Brickwork • Plaster • Wood • Painted wood • Aluminium • uPVC

ENVIRONMENTAL

Shelf life:	18 months
Storage:	In dry conditions between +5°C to +25°C
Specification compliance:	EN ISO 11600
Emissions certification:	EMICODE [®] EC1 PLUS - very low emissions
Emissions certification:	A+ Indoor Air Comfort GOLD [®]
UKCA / CE mark:	BS EN 15651

 **MADE IN BRITAIN**[®]

Visit www.ct1.com or call 028 3083 4892

C-Tec N.I Limited - Head Office: Unit 6 Ashtree Enterprise Park, Newry, Co Down, Northern Ireland BT34 1BY

C-Tec N.I Limited take every care to ensure that the product design, descriptions, specifications and techniques of constructing our products are accurate at the date of printing. We constantly strive to improve our products and this may result from time to time in changes to our ranges. Please check that design, descriptions, specifications and techniques of construction described in this brochure are still valid at the time of purchase. Colours in this document are as accurate as the print process will allow. © C-Tec N.I Limited 2023. All rights reserved. No part of this publication may be produced or transmitted in any form or by any means electronic, mechanical, photocopying, recordings or otherwise or stored in any retrieval system of any nature without the written permission of the copyright holder and the publisher.

Printed August 2023



A versatile acrylic based premium grade filler and caulk, FC1 is designed specifically for professional users and utilises scientific advancements in elastomer technology.

Surfaces must be clean and free from loose material, standing water or contaminants which may otherwise impair the bond. FC1 Filler & Caulk should not be applied in temperatures below 5°C, or in areas of constant water immersion.

Non-porous surfaces such as aluminium should be cleaned with a suitable product.

Apply FC1 Filler & Caulk firmly into the joint using an application gun:

- Cut the cartridge at the nose above the tread.
- Screw on the nozzle.
- Cut off the nozzle to the desired dimensions.
- Slot the cartridge into the application gun and pull the trigger to express product.
- Ensure a good solid fill is achieved.

Once applied, FC1 Filler & Caulk can be tooled to required finish. Sanding is not required.

Surrounding surfaces and tools can be cleaned with water.

For application where some movement will be exhibited i.e. larger construction joints, the minimum joint dimensions should be 6mm x 6mm with the maximum dimensions being 25mm wide by 12mm deep.

Depending on application, FC1 Filler & Caulk can be easily painted over with waterborne paints in as little as one hour - and with solvent paints once it is fully cured.



Visit www.ct1.com or call 028 3083 4892

C-Tec N.I Limited - Head Office: Unit 6 Ashtree Enterprise Park, Newry, Co Down, Northern Ireland BT34 1BY

C-Tec N.I Limited take every care to ensure that the product design, descriptions, specifications and techniques of constructing our products are accurate at the date of printing. We constantly strive to improve our products and this may result from time to time in changes to our ranges. Please check that design, descriptions, specifications and techniques of construction described in this brochure are still valid at the time of purchase. Colours in this document are as accurate as the print process will allow. © C-Tec N.I Limited 2023. All rights reserved. No part of this publication may be produced or transmitted in any form or by any means electronic, mechanical, photocopying, recordings or otherwise or stored in any retrieval system of any nature without the written permission of the copyright holder and the publisher.

Printed August 2023