

Section 1 - Identification of The Material Manufacture

Company Details:

Walther Strong & Company Ltd
Unit 3, Dysart Road
Autumn Business Park
NG31 7DD

Phone: 01780 437222

Website: www.waltherstrong.com

Email: enquiries@waltherstrongandco.com

Section 2 - Product Description

M50+ Hybrid PIB high performance Morphing rubber adhesive compound which is self-healing and a complete sealing tape designed specifically for incised and rough timbers.

This product is largely used as an excellent protection in many landscaping applications requiring longevity.

Section 3 - Applications

The Walther Strong HD Post Tape is designed for use as an overlap tape to seal exposed areas and joints on timber, effectively preventing air, moisture, and water ingress. It is ideal for protecting timber against water-related damage, including rot and microbial growth such as mould.

This product is suitable for use in high-moisture environments and can be applied to damp timber. When overlapped onto itself, it creates a complete and durable water seal.

Section 4 - Compatibility

Very good adhesion to smooth, rough and incised timbers and most other surfaces commonly used in construction materials including polycarbonate and plastisol coated sheeting.

Please contact our technical department for seal and pull test results.

Section 5 - Technical Data

Technical data	Results
Colour	Dark Grey
Dimensions	200mm wide x 10m long
Shelf life	24 months
Life expectancy	In excess of 25 years
U.V. Resistance	Excellent
Service temperature range	-42 to +93 degrees (c)
Application temperature	+5 to +35 degrees (c)

Section 6 - Key Features

Initial adhesion/track	5/5	5/5	Water-proof
Final adhesion	5/5	5/5	Weather-proof
Dimensional stability	5/5	5/5	Self-sealing ability