


DATASHEET



T8BLED25

230V 50W Twin LED Batten 1525mm (5ft) 4000K

www.mlaccessories.co.uk



| MLA PART CODE | T8BLED25 |
|-------------------------------|--|
| DESCRIPTION | 230V 50W Twin LED Batten 1525mm (5ft) 4000K |
| NET WEIGHT (KG) | 2.97 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 1525 Width - 95 Projection - 85 |
| CONSTRUCTION | Construction - Pressed steel Construction 2 - & polycarbonate |
| CLASS | I |
| IP RATING | IP20 |
| WATTAGE (W) | 50 |
| LAMP TECHNOLOGY | LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 5250 |
| LUMENS LIGHT SOURCE ONLY (LM) | 6535 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 102 |
| CIRCUIT WATTAGE (W) | 48.62 |
| CCT | 4000K |
| LIGHT COLOUR | Cool White |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.221 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.749 |
| PST-LM | 0.033 |
| BEAM ANGLE (DEGREES) | 120 |
| LIFE SPAN (HRS) | 30,000 |

| | |
|--|---|
| L70B50 LIFESPAN (HRS) | 50,000 |
| DIMMABLE | No |
| OPERATING TEMPERATURE | -15~45°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE ENTRY (MM) | 20 |
| CABLE GLAND INCLUDED | No |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 50W OUTPUT VOLTAGE - 29-43V OUTPUT CURRENT - 1200mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90.45 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -15~45°C CASE TEMPERATURE (Tc) - 70°C |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5055832934585 |

Date Created: 08/03/2023 16:47

